



TUXIN POWER DISTRIBUTION UNIT

- ✓ Reliable rack power distribution
- ✓ 100% tested for reliability and functionality
- ✓ Simple and convenient configuration options for cord length and chassis colors

Customer	Comtec
Product Name	Tuxin PDU
Series model	TX – IEC Series

SPECIFICATION

No	Item	Specification	
		32A	63A
1	Model	TX-IEC-32A-PDU	TX-IEC-63A-PDU
2	Color option		
3	Socket Type	IEC60309/C13,C19,with lock	
4	Display screen	Voltage and current	
5	Interior Connection Wire	Cooper bar	
6	Socket QTY	20* IEC320 C13 ; 4* IEC320 C19	
7	Power Input	32A IEC 2P+E male and female plug from bottom IP44	63A IEC 2P+E male and female plug from bottom IP44
8	Bracket Install	Vertical installation by sliding Front/rear area at both side of rack	
9	Cable with plug	3G*6mm ² *3m with 32A IEC 2P+E male and female plug	3G*10mm ² *3m with 63A IEC 2P+E male and female plug
10	Protection Function	2*16A circuit breaker for each bank. Power indicator light for each bank	2*32A circuit breaker for each bank. Power indicator light for each bank
11	Case material and color	Aluminum case with black coating	
12	Cable Specification	3x6mm ² ; 3m length	3x10mm ² ; 3m length
13	Product Size (can be customized)	1394x56x44.5mm	
14	Rating current	32A	63A
15	Max current	32A	63A
16	Max power	8KW	
17	Rating voltage	220-250VAC 50-60Hz input	
18	Safety Authentication	CE; RoHS	
19	Warranty	3 years	
20	Working condition	Tem 0 ~ 45 °C/ Humidity 5% ~ 95% (non condense)	