



## TUXIN SMART POWER DISTRIBUTION UNIT

- ✓ Reliable rack power distribution
- ✓ 100% tested for reliability and functionality
- ✓ Simple and convenient configuration options for cord length and chassis colors

Customer	<b>Comtec</b>
Product Name	<b>Tuxin PDU</b>
Series model	<b>TX – IEC Series</b>

### SPECIFICATION

No	Item	Specification
1	Model	TX-IEC-32A-IPDU
2	Color option	
3	Socket Type	IEC60309/C13,C19,with lock
4	Display screen on top	Voltage, current, capacity, consumed energy, temperature and humidity
5	Interior Connection Wire	Cooper bar
6	Socket QTY	18* IEC320 C13 ; 6* IEC320 C19
7	Power Input	32A IEC 2P+E male and female plug from bottom IP44
8	Bracket Install	Vertical installation by sliding Front/rear area at both side of rack
9	Cable with plug	3G*6mm <sup>2</sup> *3m With 32A IEC 2P+E male and female plug
10	Control configuration	<ul style="list-style-type: none"> <li>▪ Monitored with SNMP và HTTP/HTTPS standard ,</li> <li>▪ ≥ 4 unit master slave</li> <li>▪ Setup alert for current rate</li> <li>▪ detailed function pls see IPDU user manual</li> </ul>
11	Protection Function	2*16A circuit breaker for each bank.
12	Case material and color	Aluminum case with black coating
13	Cable Specification	3x6mm <sup>2</sup> ; 3m length
14	Product Size (can be customized)	1536x56x44.5mm
15	Rating current	32A
16	Max current	32A
17	Max power	<b>8KW</b>
18	Rating voltage	220-250VAC 50-60Hz input
19	Safety Authentication	CE; RoHS
20	Warranty	3 years
21	Working condition	Tem 0 ~ 45 °C/ Humidity 5% ~ 95% (non condense)